

3通球阀 气动 3 way ball valve

S4 I PNE

PO-NC¹
PO-NO²
PO-DA³

- L或T型阀芯
- 阳极电解铝
外壳配环氧树脂粉末涂层端盖

- 任意位置安装
- 旋转角: 90°, +/- 10°
- 整体式可视阀位指示
Stellungsanzeige

- 附件
- 限位开关
 - 电磁先导阀

- L or T ball
- Aluminium anodised body with aluminium epoxy powder coated end caps
- Any installation position
- Rotation angle 90°, +/- 10°
- Integrated optical position indication

- Accessories
- Limit switch box
 - Solenoid valve



- 1 单作用: 常闭
Single acting: failsafe close
- 2 单作用: 常开
Single acting: failsafe open
- 3 双作用
Double acting

材料 Models	密封 Seals	尺寸 Dimensions	PN	连接方式 Connections
PVC-U	EPDM, FPM PTFE	DN10 / d16 3/8" - DN50 / d63 / 2"	16	承插粘结 外插粘结 螺纹连接 法兰连接 PE承插焊接 PE对焊连接 solvent cement socket solvent spigot threaded socket flange fusion socket PE fusion spigot PE
PP	EPDM, FPM PTFE	DN10 / d16 3/8" - DN50 / d63 / 2"	10	承插焊接 对焊连接 螺纹连接 法兰连接 fusion socket fusion spigot threaded socket flange
PVDF	FPM PTFE	DN10 / d16 3/8" - DN50 / d63 / 2"	6	承插焊接 对焊连接 螺纹连接 法兰连接 fusion socket fusion spigot threaded socket flange

外型尺寸 Dimensions	d	DN	G	L	L1	A	D	H	B	Y	C	Z*	t*
	16	10	3/8"	152	158	100	53	72	40	52,8	50	105,5-109	14,5-16,5
	20	15	1/2"	162	168	100	53	72	40	52,8	50	105,5-109	14,5-16,5
	25	20	3/4"	191	197	120	70	81,5	51,5	63	60	126-129	17-20
*根据材质 *depend on material	32	25	1"	200	206	120	70	81,5	51,5	63,5	60	127-130	19,5-22,5
	40	32	1 1/4"	249	255	162	101	107,5	73	84,5	81	169-178	22-27,5
	50	40	1 1/2"	261	267	162	101	107,5	73	85,5	81	171-181	25-31,5
	63	50	2"	296	302	181	121,5	116,5	85	96,5	90,5	193-206	29-38,5

