

隔膜阀 气动 Diaphragm valve

T4 I PNE

PO-NC¹
PO-NO²
PO-DA³

- 执行机构塑料外壳
- 可视阀位指示
- 不锈钢进气/排气口
- 电磁先导阀接口 NAMUR (适用于 K122和K123型)

- 附件
- 阀位指示开关
 - 2位3通或2位5通式电磁先导阀
 - 紧凑型定位器 4-20mA/0-10V

- Plastic actuator body
- Visual position indication
- Insert/outlets stainless steel
- NAMUR adaptor for solenoid valve (with adaptation for K122 and K123)

- Accessories
- Electrical position indication
 - Solenoid valve with combined 5/2 and 3/2 way function
 - Compact Positioner 4-20mA /0-10V



- 1 单作用：常闭
Single acting: failsafe close
- 2 单作用：常开
Single acting: failsafe open
- 3 双作用
Double acting

永熙机电

		膜片 Diaphragm	尺寸 Dimensions	PN	连接方式 Connections
材料 Models	PVC-U	EPDM, FPM, PTFE-coated	DN15/d20 1/2" - DN50/d63 1/2"	10	承插粘结 外插粘结 螺纹连接 法兰连接 solvent cement socket solvent spigot threaded socket flange
	PP	EPDM, FPM, PTFE-coated	DN15/d20 1/2" - DN50/d63 1/2"	10	承插焊接 对焊连接 螺纹连接 法兰连接 fusion socket fusion spigot threaded socket flange
	PVDF	EPDM, FPM, PTFE-coated	DN15/d20 1/2" - DN50/d63 1/2"	10	承插焊接 对焊连接 螺纹连接 法兰连接 fusion socket fusion spigot threaded socket flange

DN 65 - DN 125 auf Anfrage erhältlich.
DN 65 - DN 125 available on request.